



Kitemark[™] Certificate

This is to certify that:

Iceni Windows Ltd Unit 3L Moss Road Freebournes Industrial Estate Witham CM8 3UW United Kingdom

Holds Certificate Number:

KM 661008

In respect of:

BS 7412 / PAS 24 Enhanced Security PVCU Doors Fabricator

This issues the right and licence to use the Kitemark in accordance with the Kitemark Terms and Conditions governing the use of the Kitemark, as may be updated from time to time by BSI Assurance UK Ltd (the "Conditions"). All defined terms in this Certificate shall have the same meaning as in the Conditions.

The use of the Kitemark is authorized in respect of the Product(s) detailed on this Certificate provided at or from the above address.

For and on behalf of BSI:

First Issued: 22/02/2017

Gary Fenton, Global Product Certification Director

Latest Issue: 22/02/2017

Page: 1 of 3



...making excellence a habit."

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request. To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated <u>online</u>.

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK. A member of BSI Group of Companies.

Kitemark[™] Certificate

No. KM 661008

BS 7412:2007 / PAS 24:2012 - General and enhanced security performance requirements for door assemblies.

This Certificate covers the fabrication of doors from the range of profiles and components supplied by Rehau Limited under Certificate Number KM 66461.

Total 70 PVC-U Residential Door System

Fabricated and installed in accordance with the latest issue of the following Rehau Limited manual(s):

Total 70 Door System Manufacturing Specification

System description

The door assemblies are Single leaf, open in or open out, hinged on outer frame, internally beaded with BS EN 1279-2 compliant IGU(s), laminated on one pane to class P1A or panelled infill(s), with or without welded or mechanically fixed midrails (either glass/midrail/panel, panel/midrail/panel, glass/midrail/glass, full panel or full glass), with either standard or mechanically fixed low threshold and of otherwise fully welded construction.

Size Limitations and Performance Characteristics

Door Type	Length (mm) - Maximum	Height (mm) - Maximum (including sill)	Air Permeability classification	Watertightness classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1:2009 (except *)			
Overall dimensions for doors with approved outer frame and sash profiles:									
Single leaf Open Out	1000	2200	-	-	-	1200 Special*			
Single leaf Open In	1000	2200	-	-	-	800*			

* Exposure category as given in Table 1 of PAS 23-1:1999

First Issued: 22/02/2017

Latest Issue: 22/02/2017

Page: 2 of 3

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.

To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated online.

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK. A member of BSI Group of Companies.

Kitemark[™] Certificate

No. KM 661008

BS 7412:2007 / PAS 24:2012 - General and enhanced security performance requirements for door assemblies.

This Licence covers the fabrication of doors from the range of profiles and components supplied by Rehau Limited under Licence Number KM 66461.

Total 70 PVC-U French Door System

Fabricated and installed in accordance with the latest issue of the following Rehau Limited manual(s):

Total 70 Door System Manual

System description

The door assemblies are Double leaf, open in or open out, hinged on outer frame, internally beaded with BS EN 1279-2 compliant IGU(s), laminated on one pane to class P1A, with welded standard threshold.

Size Limitations and Performance Characteristics

Door Type	Length (mm) - Maximum	Height (mm) - Maximum (including sill)	Air Permeability classification	Watertightness classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1:2009 (except *)			
Overall dimensions for doors with approved outer frame and sash profiles:									
Double leaf Open Out	1800	2200	-	-	-	800X*			
Double leaf Open In	1800	2200	-	-	-	800X*			

* Exposure category as given in Table 1 of PAS 23-1:1999

First Issued: 22/02/2017

Latest Issue: 22/02/2017

Page: 3 of 3

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request. To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated <u>online</u>.

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK. A member of BSI Group of Companies.