

Please beware: bold options are processed automatically

Orders will processed and automatically manufactured after 24 hours

Rehau Heritage Vertical Slider - Classic

Viewed From Outside

	□Orde	r ⊡Q	uote	2	Rehau Heritage Vertical Slider - Classic																Viewed From Outside					
						Invoice name & address:								lease sel uarantee dvised a	to deliv	er on th	e same o		Page: of							
46 Stepfield Road, Witham, Essex, CM8 3TH														Deliver to Invoice address Deliver to site Collection							tion	Reference:				
Tel: 01376 519279 Fax: 01376 515669 Tel:						Tel: Fax:								Delivery address:								Date:				
Email: orders@iceniwindows.co.uk						Email:																	Date required:			
	Glazir	Ig	Sash Constructi				tion Frame Head			Frame Colour				Bead Type and Spacer bar Colour Gas				Gaske	ket Colour			Furniture Colour				
Glaze	ed	A Rated	w	Welded Sash			Welde	d	0	White Rosewood				Ogee Black gkt & bar				Black	Black gkt			🗋 White				
28mm	Double	B Rated						C	Cream White Foil												Chrome					
								G	☐Golden Oak												Gold					
Item	Overall size	(inc sill etc)	Mullic		Transom		rop	Qty .	Total sill		Sill type		Run thru	hru Deep bot rail joint No		No Deep	Trav	vel Restrictor (Air			T/vent		ntion	Astragal bar		
no	Width	Height	brea	k = Gla	ss = S	plit	Other:	Quy	length	Stub	Integ	225mm	Sash Horn	Weld	Mech	bot rail	25mm	n 50mm 75mm		100mm	Top Sas	sh		Grid	Single V	
1				= Gla	ss C	כ				Stub																
2				= Gla	ss (כ				Stub	0	0		0												
3				= Gla	ss C	כ				Stub	0	0	0		0		0	0								
4				= Gla	ss C	כ				Stub																
5				= Gla	ss (כ				Stub	0						0	0								
6	-			= Gla	ss C	כ				Stub					0			0				6				
7				= Gla	ss ()				Stub	0				0		0									
8				= Gla	ss (כ				Stub	0															
1-Loc:		2-Loc:				1	_oc:		,	4-Loc:			<u> </u>	5-Loc:				6-Loc:			.oc:	8-Loc:		\square		
	1			1	1			<u>i</u>										1								
* 							★			▲				★			★					* •	★			
						Abbreviations: T = Toughened Glass E = Escape sash (Top hung)				Frame construction will be of Rehau profiles, welded head frame, welded sash & grooved joints, internally glazed with co-extruded black gaskets. Deep Bott Rail as std. 1 x Cam lock 0-599 width, 2 x Cam lock over 600 width. 2 x Pole eye to top sash, 2 x Sash hooks to bottom sash. Ogee bead. Pre-tensioned spring balances. Slim sash top, medium sash bottom. Reinforcing to Iceni Windows Ltd specification.													r want irements.			