EXTERNAL DOORS

Letters A-F



Features

- Designed for Panel, Timber PVCu and Composite Doors Flexible use
- Supplied with colour coordinated screws Perfectly matching hardware, even down to the smallest details
- Classic design with a contemporary twist Create a elegant and stylish front door


















EXTERNAL DOORS


Letters A-F

Ordering Details							
Letters A-F							
Finish	Part No.						
	Α	В	C	D	E	F	
Hardex Chrome	4B004	4B054	4B104	4B154	4B204	4B254	
Hardex Satin	4B005	4B055	4B105	4B155	4B205	4B255	
Hardex Bronze	4B006	4B056	4B106	4B156	4B206	4B256	
Hardex Gold	4B008	4B058	4B108	4B158	4B208	4B258	
Hardex Graphite	4B012	4B062	4B112	4B162	4B212	4B262	
Antique Black	4B009	4B059	4B109	4B159	4B209	4B259	
White	4B000	4B050	4B100	4B150	4B200	4B250	
Black	4B001	4B051	4B101	4B151	4B201	4B251	
Silver	4B002	4B052	4B102	4B152	4B202	4B252	









2 x Screws Provided Per Letter



Technical Information

Corrosion resistance

Meets the requirements of BS EN 1670:2007 Grade 5 (480 hours)

Material Specification	
Letters:	High quality Zinc
Coatings:	Hardex Chrome, Hardex Satin, Hardex Bronze, Hardex Gold, Hardex Graphite, Antique Black, White and Silver
Screws:	Includes 2 X M3.5 x 25mm colour coordinated countersunk flat head screw

Maintenance

For continued protection of the quality finish and appearance, Fab&Fix advise routine cleaning of all our external hardware. Moving parts should also be lightly lubricated at least twice a year. This procedure is particularly essential if products are used within a 25-mile radius of coastal areas or close proximity to building sites or large industrial areas, where more frequent cleaning may be required to prevent the accumulation of corrosive contaminants.

Packaging

Letters

Individually bagged with screws and care instructions. 10 in an outer box.

All dimensions are in mm and are nominal. Fab&Fix reserves the right to change specification without notice It is the responsibility of the door manufacturer to ensure that the finished product meets any required safety and performance specification.