□ Order □ Quote					Rehau Heritage Classic Sli							lider - Victorian 3 Part							Viewed From Outside				
Invoice name					e name & address:						Please select one of the following delivery options, we cannot guarantee to deliver on the same date if site addresses are advised after we have confirmed the delivery date.							Page: of					
46 Stepfield Road, Witham, Essex, CM8 3TH											Deliver to Invoice address Deliver to site Collection						Reference:						
Tel: 01376 519279 Fax: 01376 515669 Tel:						Fax:						Delivery address:						Date:					
Email: orders@iceniwindows,co.uk																		Date required:					
Glazing Sash Construction				Fram	e Head		Frame Colour			Bead Type and Spacer bar Colour			Gasket Colour			Fumiture Colour							
Glaze	Glazed A Rated		w	Welded Sash		Welde	Welded		☐ White ☐ Rosewood			Ovolo Black gkt & bar			Black gkt			☐ White			)		
28 <sub>mm</sub> Double B Rated						+ = -	☐ Cream ☐ White Foil ☐ Golden Oak													☐ Chror	ne		
Item no	Overall size Width	ze (inc sill etc) Mullion Transon break = Glass = Splii		<del></del>	rop Qty		otal sill length Sill type Stub 225mr		Run thru Sash Hon	Travel Restrictor (Air gap)  25mm   50mm   75mm   100mm		NO Deep bot rail	T/vent Top Sash	T/vent op Sash		Glass description			gal bar Single				
1	Widti	riegric		= Gla	<u> </u>	Outer.		- 3	Stub				John	7311111		DOCTAIL						Grid	
				61-					GLI-		-												
2				= Gla	ss 🗆				Stub														
3				= Gla	ss 🗆				Stub														
4				= Gla	ss 🗆				Stub														
5				= Gla	ss 🗆				Stub														
6				= Gla	ss 🗆				Stub														
1-Loc: 2-Loc: 3-Loc:					3-Loc:	oc:			4-Loc:				5-Loc:			6-Loc:							
Fixed VS Sash	VS ▼		Fixed VS Sash	vs Vs			Fixed VS Sash	Fixed VS Sash	1	<b>,</b>	Fixed VS Sash	Fixed VS Sash	+		Fixed VS Sash	Fixed VS Sash	+		Fixed VS Sash	Fixed VS Sash	1	,	Fixed VS Sash
Fixed VS			Fixed VS	Fixed VS			Fixed VS	Fixed VS			Fixed VS	Fixed VS			Fixed VS	Fixed VS	•		Fixed VS	Fixed VS	4		Fixed VS

Abbreviations: T = Toughened Glass E = Escape sash (Top hung)

Sash

Sash

Sash

Sash

Sash

Frame construction will be of Rehau profiles, welded head frame, welded sash & grooved joints, internally glazed with co-extruded gaskets. Deep Bott Rail as std. 1 x Cam lock 0-599 width, 2 x Cam lock over 600 width. 2 x Pole eye to top sash, 2 x Sash hooks to bottom sash. Ogee bead. Pre-tensioned spring balances. Slim sash top, medium sash bottom. Reinforcing to Iceni Windows Ltd specification. Glazing beads: As standard beads will accept only a 28mm unit

Sash

Sash

Sash

Sash

Important: Before ordering please ensure that you are familiar with our products and specifications as we will not accept responsibility for want of knowledge in the event that items do not meet with your requirements. Ordering these products you are automatically acknowledging our standard Terms and Conditions of Sale.

Sash

Sash

Sash