		er 🗆 Quote			Rehau Heritage Vertical Slider - Victorian													Viewed From Outside					e
ICENI WINDOWS & DOORS					Invoice name & address:							Please select one of the following delivery options, we cannot guarantee to deliver on the same date if site addresses are advised after we have confirmed the delivery date.							Page:		of		
46 Stepfield Road, Witham, Essex, CM8 3TH											☐ Deliver to Invoice address ☐ Deliver to site ☐ Collection							Reference:					
Tel: 01376 519279 Fax: 01376 515669 Tel:						Fax:				Delivery address:							Date:						
Email: orders@iceniwindows.co.uk																		Date required:					
	Glazi	ing	h Constru	truction Frame Head				Frame Colour			Bead Type and Spacer bar Colour				Gasket Colour			Furniture Colour					
Glaze	ed	☐ A Rated	Mechani	cal Sash	Mechanical		□w	□White		Rosewood		Ovolo Black gkt & bar			Black gkt			☐ White					
28mm	Double	☐B Rated						□Cr	ream	am White Foil		Ovolo Grey gkt & bar			☐ Grey gkt			☐ Chrome					
								□G	Golden Oak				Ovolo White gkt & bar			☐ White gkt			Gold				
Item		e (inc sill etc)	Mullion		Transom	(m		Total sill length		type Run thru				+	NO Deep bot rail	T/vent Top Sash	Glass description			Astragal b			
no	Width	Height	break	= Glas	ss = Split	Other:		length	Stub	225mm	Sash Horn	25mm	50mm	75mm	100mm	bot rail	Top Sash					Grid	Single V
1				= Glas	ss 🗆				Stub														
2				= Glas	ss 🗆				Stub														
3				= Glas	ss 🗆				Stub														
4				= Glas	ss 🗆				Stub														
5				= Glas	ss 🗆				Stub														
6				= Glas	ss 🗆				Stub														
7				= Glas					Stub														
8				= Glas					Stub						<del>                                     </del>	_						+	
°				- Gias					Stub														
1-Loc:		2-	-Loc:		3-Loc:			4-Loc:			5-Loc:			6-Loc:			7-Loc:	8-Loc:					
<b>+</b>				<b>+</b>	<b>+</b>				<b> </b>			+				+			<b>+</b>		<b>+</b>		
	<u>†</u>			<b>†</b>								<u> </u>				<u>†</u>			<u>†</u>				
				Abbreviations: T = Toughened Glass E = Escape sash (Top hung)				Frame construction will be of Rehau profiles, mechanical head frame & sash joints, internally glazed with co-extruded gaskets. Deep Bott Rail as std.  1 x Cam lock 0-599 width, 2 x Cam lock over 600 width. 2 x Pole eye to top sash, 2 x Sash hooks to bottom sash. Ogee bead. Pre-tensioned spring balances.  Slim sash top, medium sash bottom. Reinforcing to Iceni Windows Ltd specification.  Glazing beads: As standard beads will accept only a 28mm unit												or want uirements			