□ Ouote K2 Roof lantern Viewed From Outside □ Order Invoice name & address: Please select one of the following delivery options, we cannot guarantee to deliver on the same date if site addresses are advised after we have confirmed the delivery date. Deliver to Invoice address ☐ Deliver to site Collection Reference: 46 Stepfield Road, Witham, Essex, CM8 3TH Fax: 01376 515669 Tel: Fax: Delivery address: Date: Tel: 01376 519279 Date required: Email: orders@iceniwindows.co.uk Fmail: Finish Finial **Bar Cappings** Int Ext ■ None Int Ext Standard White Plain (pvc) PVC Anteak * Omate (pvc) Aluminium Anthracite Grey * Ball (alu) Black Brown * Cresting Roof Vents Chartwell Green * Manual Chrome handle None Cream * Plain (pvc) Manual Brass handle Golden Oak Omate (pvc) Electric Irish Oak * ☐ Infill (alu) Climate External size of upstand Mahogany Rosewood mm n/a White Foil RAL * * Extended Lead Time Glazing Polycarbonate Glass 4-16-4 Toughened - All Ecoclean & Warm Edge bar & Argon **External face** 25 35 Blue Green Neutral U Value of upstand Unglazed 1.2 61% Low E 45 Clear 67% 1.0 ☐ Bronze 80% 78% 67% Sunshield & 4S 1.0 **Specification** □ Opal **Percentages are Solar Reflection** External size of upstand mm K2 Pivot Eaves Beam Lantern roof system ☐ Bronze/ Opal Roof Pitch degrees Heatguard No gutters are incorporated into the roof lowering the overall height of the lantern Height Restriction (Inc Crest) mm External upstand sizes are required Roof construction will be of K2 roofing profiles, externally glazed Important: Before ordering please ensure that you are familiar with our products and specifications as we will not accept responsibility for want with co-extruded gaskets. of knowledge in the event that items do not meet with your requirements. Ordering these products you are automatically acknowledging our Double glazed, beads will accept only a 24mm unit

standard Terms and Conditions of Sale.