□ Order □ C	Quote	Conservatory - K2 Roof - Rehau 70mm								Viewed From Outside		
ICE.	DOORS	Invoice name & address:			Please select one of the following delivery options, we cannot guarantee to deliver on the same date if site addresses are advised after we have confirmed the delivery date.				Page: of			
16 Stepfield Road, Witham, Essex, CM8 3TH					Deliver to Invoice address Deliver to site Collection			Reference:				
	01376 515669				Delivery address:			Date:				
	ail: orders@iceniwindows.co.uk								Date required:			
All dimensions to	be internal cill s	size. Please indicate	rainwater outlet positions	Finish	1	Finial		Bar Cappings		Frame Options		
				Int E	Ext	☐ None		Int Ext		☐ Wall glass mat	ch roof but NEUTR	
					Standard White	☐ Plain ((pvc)	☐ PVC		A Rated	Glazed	
					Anthracite Grey *	☐ Omat	e (pvc)	☐ Aluminiı	ım	☐ B Rated	Unglazed	
					Black Brown *	☐ Ball (a	alu)			☐ Bevel Frame	☐ Bevel Sash	
					Chartwell Green *	Cresting		Roof Vents		☐ Edge Frame	☐ Edge Sash	
					Cream *	☐ None		☐ Manual Chrom	ne handle	Ogee Bead	☐ Bevel Beac	
					Golden Oak	☐ Plain ((pvc)	☐ Manual Brass	handle	Sash Hooks	☐ No Hooks	
					☐ Irish Oak *	☐ Omat	e (pvc)	Electric		☐ No Cill & FD	95mm Cill	
					Mahogany	☐ Infill ((alu)	Climate		150mm Cill	☐ 180mm Cil	
					Rosewood	Lean-	Too Firrings			Furniture Colo	ur	
				r	n/a White Foil	☐ Bi-Fold	d Heavy Duty	Ring Beam		Antique Black		
					RAL*	Gable Support Beam				☐ Black ☐ Gra		
				* Exte	nded Lead Time	Box G	utter Width	Small Large	e	☐ Bronze	☐ Satin	
						Tie Ba	ars	3 Way 5 Wa	iy	☐ Chrome	☐ White	
				Glazir	ng					☐ Copper	☐ Smoke	
				Polyca	rbonate Gla	Glass 4-16-4 Toughened - All Ecoclean & Warm Edge bar			Argan	Gold	☐ Monkey	
				25 3			Neutral		U Value	Transom Drop:		
						61%		Low E	1.2	Door options		
						67%		4S	1.0	Threshold 72mm Pvc	Low PvcA	
						80% 78%	67%	Sunshield & 4S	1.0	Open Out		
						ercentages are	Solar Refle	ection			- .	
Pitch degre	Bronze/ Opal					Restrictor						
	to underside o	of wall plate	to top of cresting		Heatguard					Hinge Hooks		
W	W	W	w w		W	W		W		Joiner		
:	:] :[: :		:	:		:		2mm PVC	24mm Alu	
										Bay Poles		
										135 Fixed will be	used 133 to 137	
										150 Fixed will be	used 148 to 152	
:1	21	1 11	1 21 1 21		1 11			1 21		150 I Med Will be		

Standard Specification:
Large frame to head of all products
All cills reinforced
300mm Homs added to all cills
Toughened glass to all units

Abbreviations:

D = Dummy sash
Frame construction joints, internally glated to all casements, 9 locks, flag hinges, 1 fab and Fix furniture.

As standard frame

Frame construction will be of Rehau 70mm profiles, fully welded & grooved joints, internally glazed with black co-extruded gaskets. Kenrick Shootbolts to all casements, 90 degree stays to side hung casements, Kenrick door locks, flag hinges, twin handles to french doors both with shootbolts. Fab and Fix furniture.

As standard frame beads will accept only a 28mm unit.

Important: Before ordering please ensure that you are familiar with our products and specifications as we will not accept responsibility for want of knowledge in the event that items do not meet with your requirements. Ordering these products you are automatically acknowledging our standard Terms and Conditions of Sale.