

☐ Order ☐ Quote

Conservatory - Ultraframe Roof - Rehau 70mm

Viewed From Outside



46 Stepfield Road, Witham, Essex, CM8 3TH

Tel: 01376 519279 Fax: 01376 515669

Email: orders@iceniwindows.co.uk

Invoice name & address:

Tel:

Fax:

Email:

Please select one of the following delivery options, we cannot guarantee to deliver on the same date if site addresses are advised after we have confirmed the delivery date.

☐ Deliver to Invoice address☐ Deliver to site☐ Collection

Delivery address:

Page: of

Reference:

Date:

Date required:

All dimensions to be internal cill size. Please indicate rainwater outlet positions

Pitch dearees

Minimum Height mm
to underside of wall plate

Maximum Height mm
to top of cresting

Finish		Finial		Bar Cappings	
Int	Ext	☐ None		Int	Ext
☐ ☐	Standard White	☐ Plain (pvc)		☐ ☐	PVC
☐ ☐	Anthracite Grey *	☐ Ornate (pvc)		☐	Aluminium
☐ ☐	Black Brown *	☐ Ball (alu)			
☐ ☐	Chartwell Green *	Cresting		Roof Vents	
☐ ☐	Cream *	☐ None		☐	Manual Chrome handle
☐ ☐	Golden Oak	☐ Plain (pvc)		☐	Manual Brass handle
☐ ☐	Irish Oak *	☐ Ornate (pvc)		☐	Electric
☐ ☐	Mahogany	☐ Infill (alu)		☐	Climate
☐ ☐	Rosewood	☐ Lean-Too Firrings			
☐ ☐	n/a White Foil	☐ Bi-Fold Heavy Duty Ring Beam			
☐ ☐	RAL *	☐ Gable Support Beam			
* Extended Lead Time		Box Gutter Width	☐ Small	☐ Large	
		Tie Bars	☐ 3 Way	☐ 5 Way	
Glazing					
Polycarbonate		Glass 4-16-4 Toughened - All Ecoclean & Warm Edge bar & Argon			
25	35	Blue	Green	Neutral	U Value
☐ ☐	Unglazed	☐ 61%	☐	☐ Low E	1.2
☐ ☐	Clear	☐ 67%	☐	☐ 4S	1.0
☐ ☐	Bronze	☐ 80%	☐ 78%	☐ 67%	Sunshield & 4S 1.0
☐ ☐	Opal	Percentages are Solar Reflection			
☐ ☐	Bronze/ Opal				
☐ ☐	Heatguard				

Frame Options		
☐ Wall glass match roof but NEUTRAL		
A Rated	Glazed	
☐ B Rated	☐ Unglazed	
☐ Bevel Frame	☐ Bevel Sash	
☐ Edge Frame	☐ Edge Sash	
Ogee Bead	☐ Bevel Bead	
Sash Hooks	☐ No Hooks	
☐ No Cill & FD	☐ 95mm Cill	
150mm Cill	☐ 180mm Cill	
Furniture Colour		
☐ Antique Black		
☐ Black	☐ Graphite	
☐ Bronze	☐ Satin	
☐ Chrome	☐ White	
☐ Copper	☐ Smoke	
☐ Gold	☐ Monkey	
Transom Drop:		
Door options		
Threshold		
72mm Pvc	☐ Low Pvc	☐ Alu
☐ Open Out	☐ Open In	
☐ Master Left	☐ Master Right	
☐ Restrictor		
☐ Hinge Hooks		
Joiner		
☐ 2mm PVC	☐ 24mm Alu	
Bay Poles		
135 Fixed will be used 133 to 137		
150 Fixed will be used 148 to 152		
☐ Bay Jacks to all poles		

Diagram illustrating the process of drawing a square, showing eight frames (Frame A to Frame H) with dimensions W (Width) and H (Height).

Each frame shows a square with dashed lines indicating the width (W) and height (H). The width is consistently 10 units, and the height is consistently 10 units. The frames show the square being drawn from left to right, with the right edge moving from left to right across the frames.

Standard Specification:

Large frame to head of all products
All cills reinforced
300mm Horns added to all cills
Toughened glass to all units

Abbreviations:

D = Dummy sash

Frame construction will be of Rehau 70mm profiles, fully welded & grooved joints, internally glazed with black co-extruded gaskets, Kenrick Shootbolts to all casements, 90 degree stays to side hung casements, Kenrick door locks, flag hinges, twin handles to french doors both with shootbolts. Fab and Fix furniture.

As standard frame beads will accept only a 28mm unit.

Important: Before ordering please ensure that you are familiar with our products and specifications as we will not accept responsibility for want of knowledge in the event that items do not meet with your requirements. Ordering these products you are automatically acknowledging our standard Terms and Conditions of Sale.