□ Order □ Quote		Orangery Roof - Lek	a Systems - Reha	ıu 70mm		١	/iewed Fro	m Outside		
ICENI	Invoice name & address:		Please select one of the following delivery options, we cannot guarantee to deliver on the same date if site addresses are advised after we have confirmed the delivery date.			Page: of				
46 Stepfield Road, Witham, Essex, CM8	2TU		Deliver to Invoice ad	_	-	Reference:				
		- I								
Tel: 01376 519279 Fax: 01376 5156		Tel: Fax:		Delivery address:		Date:				
Email: orders@iceniwindows.co.uk	Email:					Date requir	red:			
All dimensions to be interm	al cill size. Please indicate rainwater	outlet positions Ro	of Options				Frame Options	1		
		Ins	sulation Grade	Roof finish			Wall glass match roof but NEUTR			
			Leka Eco (U-Value 0.18)	Supply EPDM Membrane & kit			A Rated	Glazed		
			Leka A (U-Value 0.15)	Supply Lantem ker	b upstand (kerb thickne	ess 50mm)	☐ B Rated	Unglazed		
		Fas	scia Colour	External upstand Widt	า:		☐ Bevel Frame	☐ Bevel Sash		
			White	External updand depth:			☐ Edge Frame	☐ Edge Sash		
			Anthracite Grey	Supply Lantem roo	of		Ogee Bead	☐ Bevel Bead		
			Black	External Lantern Width:			Sash Hooks	☐ No Hooks		
			Chartwell Green	External Lantern Dept	 epth:		☐ No Cill & FD	95mm Cill		
			Golden Oak	Lantem Pitch:	itch:		150mm Cill	180mm Cill		
			Rosewood	External Lantern Colour:			Fumiture Colour Antique Black			
			No Fascia	Internal Lantern Colour:						
		Gu	tter Colour	☐ Blue easy clean gla	ass Clear easy	clean glass	Black	☐ Graphite		
			White				Bronze	☐ Satin		
			Black	Supply flat roof light	nt/s inc upstand (5 degr	ree pitch)	Chrome	☐ White		
			No gutter	External flat roof light Width: External flat roof light Depth:			Gold	☐ Monkey		
			ffit Type				1 3 3 3 3 3			
			Standard		Flat roof light quantity:		Transom Drop:			
			Extended	External flat roof light Colour:			-			
			ffit size (mm):	Internal flat roof light Colour:			_ Door options Threshold			
			asured from internal frame/ brick	☐ Blue easy clean glass ☐ Clear easy clean glas		clean glass	72mm Pvc Low Pvc			
) ,			Open Out (⊃Open In		
Pitch				DRAW POSITION OF ROOFS		ON PLAN DIAGRAM		eft Master Right		
							Restrictor			
							☐ Hinge Hooks			
W	W W	W	W	W	W		Joiner			
] [] [<u> </u>			2mm PVC	24mm Alu		
							Bay Poles			
							135 Fixed will be	used 133 to 137		
							150 Fixed will be	used 148 to 152		
I I				J	J ∓\		Bay Jacks to all p	poles		
Frame A Frame B	Frame C Frame Abbreviations: D = Dummy sash		Frame F	Frame G	Frame H	- ula a a l		e Consiliano del		
Standard Specification: Large frame to head of all products	Abbreviations: D = Dummy sash	joints, internally glazed	be of Rehau 70mm profiles, with black co-extruded gaske	ets. Kenrick Shootbolts	Important: Before order products and specifications for the average of the same of the s	ons as we wil	II not accept respo	nsibility for want		
All cills reinforced		locks, flag hinges, twin	gree stays to side hung caser handles to french doors both		of knowledge in the eve Ordering these products					
300mm Homs added to all cills		Fab and Fix fumiture.		S	standard Terms and Con			J J		
Toughened glass to all units		As standard frame bead	ds will accept only a 28mm ur	nit.						