

Please beware: bold options are processed automatically

! Orders will processed and automatically manufactured after 24 hours

| | Order | □Qι | ıote | 58mn | n Inte | ernal | lly Glaze | ed A | llum | iniu | m F | Resi | dent | ial \ | Wind | dow | / - F | IX | TUF | RES | 5 W | [LL | BE | DU | MM | 1Y SA | ISH Vie | wed Fro | m Outside | |
|---|---------|--------|-------------------|------|-------------------------|----------------|---|--|--------------|---------------|--------------|------------------------------|-------------------------------|---------------------------------|---|---|-------|-----------|--------------------------|--------|----------------------|---------------|--|--------|----------|----------------|-------------------|--|-----------|--|
| | | E | 1) | | Invoice name & address: | | | | | | | | | | | Please select one of the following delivery options, we cannot guarantee to deliver on the same date if site addresses are advised after we have confirmed the delivery date. | | | | | | | | | | | | of | | |
| 46 Stepfield Road, Witham, Essex, CM8 3TH | | | | | | | | | | | | | | | Deliver to Invoice address Deliver to site Collection | | | | | | | | | | | | Reference: | | | |
| Tel: 01376 519279 Fax: 01376 515669 Tel: | | | | | | | Fax: | | | | | | | Delivery address: | | | | | | | | | | | | Date: | | | | |
| Email: orders@iceniwindows.co.uk | | | | | | | | | | | | | | | | | | | | | | | | | | Date required: | | | | |
| | Glazing | | Fran | ne | | Sash | | | Trans | som/ r | nu ll | | | Co | olour | | | Bea | Bead & Spacer bar Colour | | | | Gasket Colour Sash Hooks | | | | | Furniture Col | our | |
| Glazed A Rated | | | AW604 43mm | | | AW614 SL Bevel | | | AW631 Fluted | | | ■ White 9910HG | | | | | | s | Square Black spacer | | | Black gkt Yes | | | Yes | ☐ Antique Bla | ck Copper | ☐ White | | |
| Unglazed B Rated | | | ☐ AW605 53mm | | | AW686 SL Step | | ped | ☐ AV | V632 F | lat | □Ar | Anthracite 7016 | | | M White Inside | | | Square, Grey spacer | | | | □ No | | | ☐ No | □Black | Gold | | |
| 28mm Double 28mm Triple | | | AW603 Oddleg 53mm | | 53mm | AW685 SL Flat | | | | | | ☐Black 9005M | | | ☐White Inside | | | e C | Square, White spacer | | | | | | | Bronze | Graphite | e Monkey Handle | | |
| | | | | | | | | | | | | □a | eam 1 | 013SG | G □ White Inside | | | е | | | | | | Chrome | Satin | ☐ Monkey Stay | | | | |
| Item Overall size (inc sil | | | | n Tr | Transom | Qty | Total sill length | | | Sill type | | | | | | | | Add-On 20 | | | | Joiner 15mm | | | T/vent o | | Glass description | | | |
| no | Width | Height | break | | drop | Qc, | length | none | 95 | | 190 | | Face | top | bott | left | right | top | bott | left | right | top | bott | left | right | Head | | | ipcion | |
| 1 | | | | | | | | | | 150 | | Base | | | | | | | | | | | | | | | | | | |
| 2 | | | | | | | | | | 150 | | Base | | | | | | | | | | | | | | | | | | |
| 3 | | | | | | | | | | 150 | | Base | | | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | _ | 150 | | Base | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | 150 | | Base | | | | | | | | | | | | | | | | | | |
| 6 | | | | | | | | | | 150 | | Base | | | | | | | | | | | | | | | | | | |
| 7 | | | | | | | | | | 150 | | Base | | | | | | | | | | | | | | | | | | |
| 8 | | | | | | | | | | 150 | | Base | | | | | | | | | | | | | | | | | | |
| 1-Loc: | | | 2-Loc: | | | 3-Loc: | | | | 4 - L0 | c: | | | | 5-Loc: | | | | | 6 | -Loc: | | | | | '-Loc: | | 8-Loc: | 8-Loc: | |
| | | | | | | | | | | | | | | | | | | | ╁ | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | J | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | R = F E = E ER = E HE = F D = C | Abbreviations: R = Restrictor E = Easy Clean ER = Easy Clean Restrictor HE = Heavy Duty Easy Clean D = Dummy Sash T = Toughened Glass | | | | oints, i rojan : aseme | interna Shootb ents, Fa | illy glaa oolts to ab and | will be of AluK 58mm profiles, n zed with black gaskets. o all casements, 90 degree stays Fix fumiture. Oddleg measured standard beads will accept only | | | | | s to s | side hui long led | ٦. | Important: Before ordering please ensure that you are familiar with our products and specifications as we will not accept responsibility for want of knowledge in the event that items do not meet with your requirements Ordering these products you are automatically acknowledging our standard Terms and Conditions of Sale. | | | | | nsibility for want your requirements. | | |